

	IS	T	-	23M	1	2	CO	1	0	-	0
Integrated Stepper Motor											
Type											
T	High torque										
Frame Size and Length											
17S	NEMA 17 Short										
17M	NEMA 17 Medium										
17L	NEMA 17 Long										
23S	NEMA 23 Short										
23M	NEMA 23 Medium										
23L	NEMA 23 Long										
34M	NEMA 34 Medium										
34L	NEMA 34 Long										
Shaft											
1	Single flat (Frame size 17 and 23 only)										
2	Double flat (Frame size 34 only)										
3	Keyway										
4	Full round										
Connector and Degree of Protection											
2	Crimp connectors, IP20										
6	M-connectors, IP65 (Frame size 23, 34 only)										
Communication											
CO	CANopen (Frame size 17, IP20 only)										
EC	EtherCAT (Frame size 17, IP65 only)										
Feedback											
1	Standard – 12-bit absolute single turn										
Brake											
0	No brake										
1	With brake (Frame size 23, 34 only)										
Options											
0	Standard: NEMA 17, 14–48V, 1.8A NEMA 23, 14–48V, 4.5A NEMA 34, 14–75V, 7A										
1	NEMA 34, 14–48V, 4.5A (IP20 only)										

For Brake options and Gearbox options, contact STXI Motion.